




Dome & Turret > G5 Dome



G5 Dome

UVC-G5-Dome

- Datasheet**
- In The Box
- Marketing Images
- Installation Guide



Mechanical

Dimensions	Ø109.2 x 64.5 mm (Ø4.3 x 2.5")
Weight	Without mount: 370 g (13.1 oz) With mount: 390 g (13.8 oz)
Enclosure material	Aluminum alloy, polycarbonate, hard-coated dome
Mount material	Polycarbonate, stainless steel
Weatherproofing	IPX4
Resistance	IK08

Optics

Sensor	5MP CMOS
Lens	Fixed focal length
View angle	H: 102.4°, V: 54.9°, D: 120.6°
Night mode	Built-in IR LED illumination and IR cut filter

Video

Resolution	4MP 2688 x 1512 (16:9)
Max. frame rate	30 FPS
Image settings	Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay

System

Processor	Dual-core Arm® Cortex®-A7 based chip
Networking interface	10/100 MbE RJ45 port
Max. power consumption	5W
Power method	PoE
Supported voltage range	37-57V DC
LED	R/G/B/W
Button	Factory reset
Mounting	Wall, ceiling mount
Ambient operating temperature	-20 to 40° C (-4 to 104° F)
Ambient operating humidity	0 to 90% noncondensing

Certifications

FCC, IC, CE

Audio**Microphone**

Yes (Can be disabled)

Speaker


Yes

Software**Web application**

UniFi Protect: Version 2.2.7 or 2.7.28 and later

Mobile app

UniFi Protect iOS™ and Android™: Version 1.10.0 and later

Stay in Touch[Subscribe](#)[Terms of Service](#) | [Privacy Policy](#) | [Legal](#) | [Cookies Settings](#)

© 2024 Ubiquiti, Inc. All rights reserved.