



Camera Security / Doorbells **G6 Entry**



^ Overview

Dimensions	176 x 45 x 29.6 mm (6.9 x 1.8 x 1.2")
IR Night Vision	5 m (16 ft)
Face Recognition	✓
Smart Detections (People, Vehicles, Animals)	✓
Resolution	5MP
Field of View	H: 100°, V: 135°, D: 180°
Audio	Two-way audio i
Weatherproofing	IP55
Tamper Resistance	IK07
Mounting	Wall mount, Gangbox mount plate, 20° wedge mount (Included) Junction box (Optional)

NFC Card & Keyfob Access	✓
Apple/Google Wallet	✓ i
Face Unlock	✓
Mobile Unlock	✓
Two-Way Intercom & Doorbell Access	✓
UniFi Application Suite	
— Protect	✓
— Access	✓

^ Performance

Networking Interface

GbE RJ45 port

Connectivity

BLE 4.1

NFC

Video

Image Settings

Color, brightness, sharpness, contrast, white balance, exposure control, 2DNR, 3DNR, NR by motion, masking, text overlay, HDR

Max. Frame Rate

Main camera: 30 FPS

Package camera: 3 FPS

Resolution

Main camera: 5MP, 1920 x 2560 (3:4)

Package camera: 8MP 3264 x 2448 (4:3)

Optics

Sensor

Main camera: 5MP CMOS

Package camera: 8MP CMOS

Lens

Fixed focal length

Night Mode

Built-in IR LED illumination and IR cut filter

^ Hardware

Max. Power Consumption	16W
Supported Voltage Range	42—57V DC
Power Method	PoE+
Processor	Quad-core Arm® Cortex®-A53 based chip
Weight	275 g (9.7 oz)
Enclosure Material	Aluminum
Mount Material	Wall mount: Stainless steel Gangbox mount plate: SGCC steel Gangbox mount cover: Polycarbonate Wedge mount: Aluminum
Button	(1) Ring button (1) Factory-reset (1) Tamper switch
LEDs	R/G/B/W Learn More
Ambient Operating Temperature	-30 to 50° C (-22 to 122° F)
Ambient Operating Humidity	5 to 90% noncondensing
NDAA Compliant	✓
Certifications	CE, FCC, IC

